



DURA-EZ TIQUE

DESCRIPTION AND BASIC USE: Proline DURA EZ-TIQUE cementitious Antiquing Product is a versatile coloring agent that can be easily applied and will hold fast to any textured concrete surface. It is sold as a powder but is designed to be mixed with water and applied as a liquid wash coat. EZ-TIQUE can be used to revitalize a weathered concrete surface or add an antique color to a freshly textured surface. It goes on quickly and easily and can be removed readily for greater control of the coloring process. This product is water-based, non-hazardous, and zero V.O.C. It comes in 42 standard colors, matching the Proline DURA CH and AR color chart, and custom colors can be matched to order for no charge.

STORAGE: Store in a cool, dry place, in temperatures below 120° F. Shelf life is approximately 1 year, but will last much longer if containers are kept tightly sealed.

COVERAGE: One 3 pound bucket of Proline EZ-TIQUE covers approximately 2000-3000 square feet.

APPLICATION: Proline DURA EZ-TIQUE is intended for professional use only. It comes in a 1 gallon pail with approximately 3 pounds of colored powder and a three-quarter cup measuring spoon wrapped in a plastic bag. To mix: pull out and open the bag of EZ-TIQUE powder, fill the 1 gallon pail with water, and mix in one full three-quarter cup measuring spoon of the powder. Use more or less of the product in one gallon of water to achieve different results in color intensity. EZTIQUE can be mixed readily with a stir stick so motorized mixing is not necessary, but the product in the container will need to be agitated periodically during application to keep the solids from settling. This settling property of EZ-TIQUE is important in reaching the desired antique effect. Before applying product to unsealed concrete, it is helpful to pre-moisten the surface with water so the liquid color will have time to even out and settle properly. The most basic technique to apply EZ-TIQUE is to simply pour the liquid color straight onto the horizontal concrete surface with a standard garden watering can, making sure to leave a uniform coat of liquid over the area to be covered. If necessary, liquid EZ-TIQUE can be spread quickly and easily with a clean push broom. Be sure to have clean water handy to spray on the surface to make sure the color spreads uniformly. EZ-TIQUE can be cleaned up readily with water while it is still wet and can be wiped off with a clean dry sponge when dry.

SEALING AND MAINTENANCE: A quality Proline sealer is recommended to protect the newly colored concrete surface. The concrete must be cleaned and thoroughly dried prior to application. Proline provides sealing products such as, DURA-SEAL HG (High Gloss finish) and DURA-SEAL MATTE (Matte finish), which are solvent-based acrylic clear sealers. Inspect annually for areas of thin or traffic-worn sealer and re-apply as necessary. Standard cleaning practices for colored concrete should be followed; schedule periodic cleaning to avoid accumulation of dirt, flatwork and floors are easily maintained by sweeping, clean spills when they occur, hose off dirt with water, and treat heavily soiled areas by wet mopping and/or scrubbing with a properly diluted, high-quality commercial grade detergent.

NOTES: Experimentation of colors and application methods is recommended, as the color of the actual product may differ. Test sections must be produced on each concrete surface. Even in a controlled environment, cements, aggregates, water content, and concrete curing methods will contribute to different results. Final color approval should be made with actual material and sealer selection; however, variation of even mock-up samples due to reproduction limitations should be expected.

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality with manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Wear rubber gloves and aprons to protect skin and wear safety eye goggles.